

VISOR RAIN OFF 100ML- 800676 - A18243



SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

>SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

> 1.1. Product identifier

Product name : VISOR RAIN OFF 100ML- 800676

Product code : A18243.

UFI : CF10-C0K6-J00E-E8P4

> 1.2. Relevant identified uses of the substance or mixture and uses advised against

Cleaner

> 1.3. Details of the supplier of the safety data sheet

Registered company name : IPONE.

Address : La Meunière .13480.CABRIES .FRANCE.

Telephone : +33 (0)4 42 94 05 65. Fax : +33 (0)4 42 94 05 66.

info@ipone.fr

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

>SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 2 (Flam. Liq. 2, H225).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Mixture for spray application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02



GHS07

Signal Word :

DANGER

Product identifiers :

603-117-00-0

PROPAN-2-OL

Hazard statements :

H225

Highly flammable liquid and vapour.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

Precautionary statements - General :

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P103

Read carefully and follow all instructions.

Precautionary statements - Prevention :

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261

Avoid breathing product.

P280

Wear eye protection.

Precautionary statements - Response :

P304 + P340

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

**VISOR RAIN OFF 100ML- 800676 - A18243**

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312

Call a POISON CENTER/doctor/.../if you feel unwell.

Precautionary statements - Disposal :

P501

Dispose of contents/container according to the local rules.

**> 2.3. Other hazards**

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances  $\geq 0.1\%$  with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

**>SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

**3.2. Mixtures**

**Composition :**

| Identification   | Classification (EC) 1272/2008  | Note | %                   |
|--|--|------|---------------------|
| INDEX: 603-117-00-0<br>CAS: 67-63-0<br>EC: 200-661-7<br>REACH: 01-2119457558-25<br>PROPAN-2-OL | GHS02, GHS07<br>Dgr<br>Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336 | [1]  | 50 $\leq$ x % < 100 |

**> Information on ingredients :**

(Full text of H-phrases: see section 16)

Substances may not have a REACH Registration No.. because they are manufactured / imported in quantities less than 1 ton / year, or they are complex substances or they are exempted from registration under REACH.

[1] Substance for which maximum workplace exposure limits are available.

**>SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. description of first aid measures**

**> In the event of exposure by inhalation :**

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of inhalation of spray mist, seek medical attention immediately, showing the packaging or label.

In case of massive inhalation transport the patient outdoors and keep him for the warmth and for the rest.

Consult doctor if symptoms develop.

**> In the event of splashes or contact with eyes :**

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

Consult a doctor with the label.

**> In the event of splashes or contact with skin :**

Lave bem a pele com água. Se a irritação persistir, chame um médico.

**In the event of swallowing :**

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**VISOR RAIN OFF 100ML- 800676 - A18243**

**4.3. Indication of any immediate medical attention and special treatment needed**

**Specific and immediate treatment :**

No data available.

**Information for the doctor :**

No data available.

---

**>SECTION 5 : FIREFIGHTING MEASURES**

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

**5.1. Extinguishing media**

Keep packages near the fire cool, to prevent pressurised containers from bursting.

**Suitable methods of extinction**

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

**Unsuitable methods of extinction**

In the event of a fire, do not use :

- water jet

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)

**> 5.3. Advice for firefighters**

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

---

**>SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For non first aid worker**

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

**> 6.4. Reference to other sections**

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**VISOR RAIN OFF 100ML- 800676 - A18243**

See Section 7 for information on safe handling.

**>SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

**Fire prevention :**

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged: always ground when decanting. Wear antistatic shoes and clothing and make floors of non-conductive

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors.

Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent vapors in every case.

It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent vapors has fallen below the exposure limits.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**> 7.2. Conditions for safe storage, including any incompatibilities**

Store receptacle in a well ventilated area.

Store in cool, dry conditions in well sealed receptacles.

**Storage**

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

**VISOR RAIN OFF 100ML- 800676 - A18243**

**>SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

**Occupational exposure limits :**

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

| CAS     | TWA :   | STEL :  | Ceiling : | Definition : | Criteria : |
|---------|---------|---------|-----------|--------------|------------|
| 67-63-0 | 200 ppm | 400 ppm |           | A4; BEI      |            |

- Germany - AGW (BAuA - TRGS 900, 02/2022) :

| CAS     | VME : | VME :                            | Excess | Notes |
|---------|-------|----------------------------------|--------|-------|
| 67-63-0 |       | 200 ppm<br>500 mg/m <sup>3</sup> |        | 2(II) |

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021) :

| CAS     | VME-ppm : | VME-mg/m <sup>3</sup> : | VLE-ppm : | VLE-mg/m <sup>3</sup> : | Notes : | TMP No : |
|---------|-----------|-------------------------|-----------|-------------------------|---------|----------|
| 67-63-0 | -         | -                       | 400       | 980                     | -       | 84       |

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

| CAS     | TWA :                            | STEL :                            | Ceiling : | Definition : | Criteria : |
|---------|----------------------------------|-----------------------------------|-----------|--------------|------------|
| 67-63-0 | 400 ppm<br>999 mg/m <sup>3</sup> | 500 ppm<br>1250 mg/m <sup>3</sup> |           |              |            |

**Derived no effect level (DNEL) or derived minimum effect level (DMEL):**

PROPAN-2-OL (CAS: 67-63-0)

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Workers.**

Dermal contact.  
Long term systemic effects.  
888 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term systemic effects.  
500 mg of substance/m<sup>3</sup>

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Consumers.**

Ingestion.  
Long term systemic effects.  
26 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Dermal contact.  
Long term systemic effects.  
319 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term systemic effects.  
89 mg of substance/m<sup>3</sup>

**Predicted no effect concentration (PNEC):**

PROPAN-2-OL (CAS: 67-63-0)

Environmental compartment:  
PNEC :

Soil.  
28 mg/kg

Environmental compartment:  
PNEC :

Fresh water.  
140.9 mg/l

Environmental compartment:  
PNEC :

Sea water.  
140.9 mg/l

Environmental compartment:  
PNEC :

Intermittent waste water.  
140.9 mg/l

Environmental compartment:

Fresh water sediment.

**VISOR RAIN OFF 100ML- 800676 - A18243**

|                                      |  |
|--------------------------------------|--|
| PNEC :                               | 552 mg/kg                                  |
| Environmental compartment:<br>PNEC : | Marine sediment.<br>552 mg/kg              |
| Environmental compartment:<br>PNEC : | Waste water treatment plant.<br>2251 mg/m3 |
| Environmental compartment:<br>PNEC : | Vermivore predators (oral).<br>160 mg/kg   |

## 8.2. Exposure controls

### Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

When spraying, wear a face shield in accordance with standard EN166.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

#### |> - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

Let the glove manufacturer advise you on the choice of gloves and their duration of use for your operating conditions

#### - Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

#### |> - Respiratory protection

Avoid inhaling vapors.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Category :

- FFP1

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

- AX

Particle filter according to standard EN143 :

- P1

Types, classes and filters for respiratory protection above are recommended in case of confrontation at concentrations higher than the exposure limits specified under 8.1. (Control parameters) .They should be adjusted according to actual conditions. they may not be necessary if the product is used outdoors or in a well ventilated area.

**VISOR RAIN OFF 100ML- 800676 - A18243**

**>SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

**Physical state**

Physical state : Fluid liquid.

**> Colour**

Unspecified

**> Odour**

Odour threshold : Not stated.

**> Melting point**

Melting point/melting range : Not specified.

**> Freezing point**

Freezing point / Freezing range : Not stated.

**Boiling point or initial boiling point and boiling range**

Boiling point/boiling range : > 35°C

**> Flammability**

Flammability (solid, gas) : Not stated.

**> Lower and upper explosion limit**

Explosive properties, lower explosivity limit (%) : Not stated.

Explosive properties, upper explosivity limit (%) : Not stated.

**Flash point**

Flash Point : 12.00 °C.

**Auto-ignition temperature**

Self-ignition temperature : Not specified.

**Decomposition temperature**

Decomposition point/decomposition range : Not specified.

**> pH**

pH : Not relevant.

pH (aqueous solution) : Not stated.

**> Kinematic viscosity**

Viscosity : Not stated.

Viscosity:  $\nu < 7 \text{ mm}^2/\text{s}$  (40°C)

**> Solubility**

Water solubility : Insoluble.

Fat solubility : Not stated.

**> Partition coefficient n-octanol/water (log value)**

Partition coefficient: n-octanol/water : Not stated.

**Vapour pressure**

Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

**Density and/or relative density**

Density : < 1

**> Relative vapour density**

Vapour density : Not stated.

**9.2. Other information**

No data available.

**9.2.1. Information with regard to physical hazard classes**

No data available.

**9.2.2. Other safety characteristics**

No data available.

**VISOR RAIN OFF 100ML- 800676 - A18243**

---

**SECTION 10 : STABILITY AND REACTIVITY**

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

**10.4. Conditions to avoid**

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

**10.5. Incompatible materials**

No data available.

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

---

**>SECTION 11 : TOXICOLOGICAL INFORMATION**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

**11.1.1. Substances**

No toxicological data available for the substances.

**> 11.1.2. Mixture**

**> Skin corrosion/skin irritation :**

Based on available data; the classification criteria are not met.

**> Serious damage to eyes/eye irritation :**

Causes serious eye irritation

**> Respiratory or skin sensitisation :**

To be translated (XML)

**> Germ cell mutagenicity :**

Based on available data; the classification criteria are not met.

**> Carcinogenicity :**

Based on available data; the classification criteria are not met.

**> Reproductive toxicant :**

Based on available data; the classification criteria are not met.

**> Specific target organ systemic toxicity - single exposure :**

May cause drowsiness or dizziness.

**> Specific target organ systemic toxicity - repeated exposure :**

Based on available data; the classification criteria are not met.

**> Aspiration hazard :**

Based on available data; the classification criteria are not met.

**> Delayed and immediate effects as well as chronic effects from short and long-term exposure**

No further relevant information available.

**11.2. Information on other hazards**



**VISOR RAIN OFF 100ML- 800676 - A18243**

**> Other information**

No further relevant information available.

**Monograph(s) from the IARC (International Agency for Research on Cancer) :**

CAS 67-63-0 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

**SECTION 12 : ECOLOGICAL INFORMATION**

**12.1. Toxicity**

**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

**12.2. Persistence and degradability**

No data available.

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Endocrine disrupting properties**

No data available.

**12.7. Other adverse effects**

No data available.

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**>SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2023 - IMDG 2020 [40-20] - ICAO/IATA 2023 [64]).

**14.1. UN number or ID number**

1993

**14.2. UN proper shipping name**

UN1993=FLAMMABLE LIQUID, N.O.S.

(propan-2-ol)

**14.3. Transport hazard class(es)**

- Classification :



3

**14.4. Packing group**

II

**VISOR RAIN OFF 100ML- 800676 - A18243**

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

| ADR/RID | Class | Code | Pack gr. | Label | Ident. | LQ  | Provis.      | EQ | Cat. | Tunnel |
|---------|-------|------|----------|-------|--------|-----|--------------|----|------|--------|
|         | 3     | F1   | II       | 3     | 33     | 1 L | 274 601 640D | E2 | 2    | D/E    |

>

| IMDG | Class | 2°Label | Pack gr. | LQ  | EMS      | Provis. | EQ | Stowage Handling | Segregation |
|------|-------|---------|----------|-----|----------|---------|----|------------------|-------------|
|      | 3     | -       | II       | 1 L | F-E. S-E | 274     | E2 | Category B       | -           |

| IATA | Class | 2°Label | Pack gr. | Passager | Passager | Cargo | Cargo | note | EQ |
|------|-------|---------|----------|----------|----------|-------|-------|------|----|
|      | 3     | -       | II       | 353      | 5 L      | 364   | 60 L  | A3   | E2 |
|      | 3     | -       | II       | Y341     | 1 L      | -     | -     | A3   | E2 |

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

**14.7. Maritime transport in bulk according to IMO instruments**

No data available.

**>SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**> Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/643 (ATP 16)
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/849 (ATP 17)

**> Container information:**

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

**> Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):**

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):  
<https://echa.europa.eu/substances-restricted-under-reach>.

**> Explosives precursors :**

The mixture does not contain any substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors.

**Particular provisions :**

No data available.

**> 15.2. Chemical safety assessment**

The chemical safety assessment has not been carried out for this mixture.

**>SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

|      |                                     |
|------|-------------------------------------|
| H225 | Highly flammable liquid and vapour. |
| H319 | Causes serious eye irritation.      |
| H336 | May cause drowsiness or dizziness.  |

**> Abbreviations and acronyms :**

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

UFI : Unique formulation identifier.

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

**VISOR RAIN OFF 100ML- 800676 - A18243**

---

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.

|> Modification compared to the previous version