WHEEL CLEANER 1L - 800656 - A18357

Date: 17/04/2023 Page 1/13 Revision: N°10 (17/04/2023)



SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

>SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: WHEEL CLEANER 1L - 800656

Product code: A18357.

UFI: 2Q10-V0ND-F00W-D9EA

> 1.2. Relevant identified uses of the substance or mixture and uses advised against

Detergent Degreaser

1.3. Details of the supplier of the safety data sheet

Registered company name: IPONE.

Address: La Meunière .13480.CABRIES .FRANCE.

Telephone: +33 (0)4 42 94 05 65. Fax: +33 (0)4 42 94 05 66.

info@ipone.fr

1.4. Emergency telephone number: +33 (0)1 45 42 59 59.

Association/Organisation: INRS / ORFILA http://www.centres-antipoison.net.

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Skin corrosion, Category 1C (Skin Corr. 1C, H314).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Detergent mixture (see section 15).

Mixture for spray application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:



GHS05

Signal Word : DANGER

Product identifiers:

014-010-00-8 DISODIUM METASILICATE

Hazard statements:

H314 Causes severe skin burns and eye damage.

 $Precautionary\ statements\ \hbox{-}\ General:$

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements - Prevention:

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302 IF ON SKIN:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

IPONE

WHEEL CLEANER 1L - 800656 - A18357

Date: 17/04/2023 Page 2/13

Revision: N°10 (17/04/2023)

Precautionary statements - Disposal:

P501 Dispose of contents/container according to the local rules.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances $\geq 0.1\%$ with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

>SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

|> Composition :

Identification	Classification (EC) 1272/2008	Note	%
CAS: 34590-94-8		[1]	$2.5 \le x \% \le 10$
EC: 252-104-2			
REACH: 01-2119450011-60			
DIPROPYLENE GLYCOL MONOMETHYL			
ETHER			
INDEX: 603-064-00-3	GHS02, GHS07	[1]	2.5 <= x % < 10
CAS: 107-98-2	Wng		
EC: 203-539-1	Flam. Liq. 3, H226		
REACH: 01-2119457435-35	STOT SE 3, H336		
1-METHOXY-2-PROPANOL			
CAS: 68439-51-0	GHS07		$0 \le x \% \le 2.5$
REACH: POLYMER	Wng		
	Skin Irrit. 2, H315		
LAURYLMYRISTYL POLYGLYCOL ETHER	Eye Irrit. 2, H319		
	Aquatic Chronic 3, H412		
CAS: 68891-38-3	GHS05		$0 \le x \% \le 2.5$
EC: 500-234-8	Dgr		
REACH: 01-2119488639-16	Skin Irrit. 2, H315		
	Eye Dam. 1, H318		
TA-A / ALCOHOLS, C12-14, ETHOXYLATED,	Aquatic Chronic 3, H412		
SULFATES, SODIUM SALTS			
INDEX: 014-010-00-8	GHS05, GHS07		$0 \le x \% \le 2.5$
CAS: 6834-92-0	Dgr		
EC: 229-912-9	Skin Corr. 1B, H314		
REACH: 01-2119449811-37	STOT SE 3, H335		
DISODIUM METASILICATE			

Specific concentration limits:

~ F		
Identification	Specific concentration limits	ATE
CAS: 68891-38-3	Skin Irrit. 2: H315 >=10%	
EC: 500-234-8	Eye Dam. 1: H318 C>= 10%	
REACH: 01-2119488639-16	Eye Irrit. 2: H319 5% <= C < 10%	
TA-A / ALCOHOLS, C12-14, ETHOXYLATED,		
SULFATES, SODIUM SALTS		

Information on ingredients:

(Full text of H-phrases: see section 16)

Substances may not have a REACH Registration No.. because they are manufactured / imported in quantities less than 1 ton / year, or they are complex substances or they are exempted from registration under REACH.

[1] Substance for which maximum workplace exposure limits are available.

WHEEL CLEANER 1L - 800656 - A18357

Date: 17/04/2023 Page 3/13

Revision: N°10 (17/04/2023)

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation:

Consult doctor if symptoms develop.

In the event of splashes or contact with eyes:

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

In the event of splashes or contact with skin:

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated aera is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing:

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Specific and immediate treatment:

No data available.

Information for the doctor:

No data available.

SECTION 5: FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist

CO2, powder of extinction or pulverized water.

Unsuitable methods of extinction

In the event of a fire, do not use:

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

WHEEL CLEANER 1L - 800656 - A18357

Date: 17/04/2023 Page 4/13

Revision: N°10 (17/04/2023)

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Neutralise with an acidic decontaminant.

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

See Section 7 for information on safe handling.

SECTION 7: HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Fire prevention:

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent vapors in every case.

It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent vapors has fallen below the exposure limits.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

Store receptacle in a well ventilated area.

Store in cool, dry conditions in well sealed receptacles.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

IPONE

WHEEL CLEANER 1L - 800656 - A18357

Date: 17/04/2023 Page 5/13

Revision: N°10 (17/04/2023)

7.3. Specific end use(s)

No data available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

- European Union (2022/431, 2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE):

CAS	VME-mg/m3:	VME-ppm:	VLE-mg/m3:	VLE-ppm:	Notes:
34590-94-8	308	50	-	-	Peau
107-98-2	375	100	568	150	Peau

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
34590-94-8	100 ppm	150 ppm		Skin	
107-98-2	100 ppm	150 ppm			

- Germany - AGW (BAuA - TRGS 900, 02/2022) :

CAS	VME:	VME:	Excess	Notes
34590-94-8		50 ppm		1(I)
		310 mg/m ³		
107-98-2		100 ppm		2(I)
		370 mg/m ³		

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021):

CAS	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	TMP No:
34590-94-8	50	308	-	-	*	84
107-98-2	50	188	100	375	*	84

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020):

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
34590-94-8	50 ppm			Sk	
	308 mg/m ³				
107-98-2	100 ppm	150 ppm		Sk	
	375 mg/m ³	560 mg/m ³			

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

TA-A / ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (CAS: 68891-38-3)

Final use: Workers.
Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 2750 mg/kg body weight/day

Exposure method: Dermal contact.

Potential health effects: Long term local effects.

DNEL: 132 µg of substance/cm2

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 175 mg of substance/m3

Final use: Consumers.

Exposure method: Ingestion.

Potential health effects: Long term systemic effects.

DNEL: 15 mg/kg body weight/day

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 1650 mg/kg body weight/day

Exposure method: Dermal contact.
Potential health effects: Long term local effects.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version: N°1 (17/04/2023)

IPONE

WHEEL CLEANER 1L - 800656 - A18357

Date: 17/04/2023 Page 6/13

Revision: N°10 (17/04/2023)

DNEL: 79 µg of substance/cm2

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 52 mg of substance/m3

1-METHOXY-2-PROPANOL (CAS: 107-98-2)

Final use: Workers.
Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 183 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 269 mg of substance/m3

Exposure method: Inhalation.

Potential health effects: Short term systemic effects.
DNEL: 553.5 mg of substance/m3

Exposure method: Inhalation.

Potential health effects: Short term local effects.
DNEL: 553.5 mg of substance/m3

Final use: Consumers. Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.
DNEL: 78 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 43.9 mg of substance/m3

DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS: 34590-94-8)

Final use: Workers.
Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.
DNEL: 283 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 308 mg of substance/m3

Final use: Consumers.

Exposure method: Ingestion.

Potential health effects: Long term systemic effects.

DNEL: 36 mg/kg body weight/day

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 121 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 37.2 mg of substance/m3

IPONE

Revision : N°10 (17/04/2023)

Date: 17/04/2023 Page 7/13

Predicted no effect concentration (PNEC):

TA-A / ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (CAS: 68891-38-3)

WHEEL CLEANER 1L - 800656 - A18357

Environmental compartment: Soil. PNEC: 7.5 mg/kg

Environmental compartment: Fresh water. PNEC: 0.24 mg/l

Environmental compartment: Sea water. PNEC: 0.024 mg/l

Environmental compartment: Intermittent waste water.

PNEC: 0.071 mg/l

Environmental compartment: Fresh water sediment.

PNEC: 0.917 mg/kg

Environmental compartment: Marine sediment. PNEC: 0.092 mg/kg

Environmental compartment: Waste water treatment plant.

PNEC: 10 g/l

1-METHOXY-2-PROPANOL (CAS: 107-98-2)

Environmental compartment: Soil.
PNEC: 4.59 mg/kg

Environmental compartment: Fresh water.
PNEC: 10 mg/l

Environmental compartment: Sea water. PNEC: 1 mg/l

Environmental compartment: Intermittent waste water.

PNEC: 100 mg/l

Environmental compartment: Fresh water sediment.

PNEC: 52.3 mg/kg

Environmental compartment: Marine sediment. PNEC: 5.2 mg/kg

Environmental compartment: Waste water treatment plant.

PNEC: 100 mg/l

DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS: 34590-94-8)

Environmental compartment: Soil. PNEC: 2.74 mg/kg

Environmental compartment: Fresh water. PNEC: 19 mg/l

Environmental compartment: Sea water. PNEC: 1.9 mg/l

Environmental compartment: Intermittent waste water.

PNEC: 190 mg/l

Environmental compartment: Fresh water sediment.

WHEEL CLEANER 1L - 800656 - A18357

Date: 17/04/2023 Page 8/13

Revision: N°10 (17/04/2023)

PNEC: 70.2 mg/kg

Environmental compartment: Marine sediment. PNEC: 7.02 mg/kg

Environmental compartment: Waste water treatment plant.

PNEC: 4168 mg/l

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

When spraying, wear a face shield in accordance with standard EN166.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- Natural latex
- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)

Let the glove manufacturer advise you on the choice of gloves and their duration of use for your operating conditions

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

Wear suitable protective clothing and, in particular, an apron and boots. These items of clothing shall be maintained in good condition and cleaned after use.

Suitable type of protective boots:

In the event of minor spatter, wear protective boots or half-boots against chemical risks in accordance with standard EN13832-2.

In the event of prolonged contact, wear boots or half-boots with liquid-chemical-resistant and waterproof soles and uppers in accordance with standard EN13832-3.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Types, classes and filters for respiratory protection above are recommended in case of confrontation at concentrations higher than the exposure limits specified under 8.1. (Control parameters) .They should be adjusted according to actual conditions, they may not be necessary if the product is used outdoors or in a well ventilated area.

>SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state

Physical state: Fluid liquid.

Colour

Unspecified

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version: N°1 (17/04/2023)

IPONE

WHEEL CLEANER 1L - 800656 - A18357

Date: 17/04/2023 Page 9/13 Revision: N°10 (17/04/2023)

Odour

Odour threshold: Not stated.

Melting point

Melting point/melting range: Not specified.

Freezing point

Freezing point / Freezing range: Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range: Not specified.

Flammability

Flammability (solid, gas): Not stated.

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%): Not stated. Explosive properties, upper explosivity limit (%): Not stated.

Flash point

Flash Point Interval : $60^{\circ}\text{C} < \text{FP} \le 93^{\circ}\text{C}$

Auto-ignition temperature

Self-ignition temperature: Not specified.

Decomposition temperature

Decomposition point/decomposition range: Not specified.

pН

pH: Not stated.

Strongly basic.

pH (aqueous solution): Not stated.

Kinematic viscosity

Viscosity: Not stated.

Viscosity: $v < 7 \text{ mm2/s } (40^{\circ}\text{C})$

Solubility

Water solubility: Dilutable.
Fat solubility: Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water: Not stated.

Vapour pressure

Vapour pressure (50°C): Below 110 kPa (1.10 bar).

Density and/or relative density

Density: > 1

Relative vapour density

Vapour density: Not stated.

9.2. Other information

No data available.

 $\textbf{9.2.1.} \ \textbf{Information with regard to physical hazard classes}$

No data available.

9.2.2. Other safety characteristics

No data available.

> Formation of explosible dust/air mixtures

Characteristic of dust particles:

Maximum pressure generated by the explosion:

Not stated.

Deflagration index (Kst):

Minimum ignition energy:

Not stated.

MEC/LEL:

Not stated.

WHEEL CLEANER 1L - 800656 - A18357

Date: 17/04/2023 Page 10/13 Revision: N°10 (17/04/2023)

>SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Avoid:

- frost

To be translated (XML)

> 10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form:

- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure between one and four hours

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

11.1.1. Substances

No toxicological data available for the substances.

11.1.2. Mixture

Skin corrosion/skin irritation:

The 'corrosive' classification is based on the low/high pH which has been confirmed by tests.

Causes severe skin burns and eye damage.

Serious damage to eyes/eye irritation:

Corrosive classification is based on an extreme pH value.

Causes serious eye irritation.

Respiratory or skin sensitisation:

To be translated (XML)

Germ cell mutagenicity:

Based on available data; the classification criteria are not met.

${\bf Carcinogenicity:}$

Based on available data; the classification criteria are not met.

Reproductive toxicant:

Based on available data; the classification criteria are not met.

Specific target organ systemic toxicity - single exposure :

Based on available data; the classification criteria are not met.

Specific target organ systemic toxicity - repeated exposure :

Based on available data; the classification criteria are not met.

Aspiration hazard :

Based on available data; the classification criteria are not met.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

No further relevant information available.

11.2. Information on other hazards

Other information

No further relevant information available.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version: N°1 (17/04/2023)

IPONE

WHEEL CLEANER 1L - 800656 - A18357

Monograph(s) from the IARC (International Agency for Research on Cancer):

CAS 75-21-8: IARC Group 1: The agent is carcinogenic to humans.

CAS 123-91-1: IARC Group 2B: The agent is possibly carcinogenic to humans.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

TA-A/ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (CAS: 68891-38-3)

Fish toxicity: ECx > 1 mg/l

Crustacean toxicity: $0.1 \le NOEC \le 1 \text{ mg/l}$

LAURYLMYRISTYL POLYGLYCOL ETHER (CAS: 68439-51-0)

Fish toxicity: EC50 mg/l

Species : Leuciscus idus Other guideline

Crustacean toxicity: EC50 mg/l

Species: Daphnia magna

OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Date: 17/04/2023 Page 11/13 Revision: N°10 (17/04/2023)

Aquatic plant toxicity: EC10 mg/l

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

TA-A / ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (CAS: 68891-38-3)

Biodegradability: no degradability data is available, the substance is considered as not degrading

quickly.

LAURYLMYRISTYL POLYGLYCOL ETHER (CAS: 68439-51-0)

Biodegradability: no degradability data is available, the substance is considered as not degrading

quickly.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

WHEEL CLEANER 1L - 800656 - A18357

Date: 17/04/2023 Page 12/13

Revision: N°10 (17/04/2023)

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

>SECTION 14: TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2023 - IMDG 2020 [40-20] - ICAO/IATA 2023 [64]).

14.1. UN number or ID number

3267

14.2. UN proper shipping name

UN3267=CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.

(disodium metasilicate)

14.3. Transport hazard class(es)

- Classification:



8

14.4. Packing group

Ш

14.5. Environmental hazards

•

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	8	C7	III	8	80	5 L	274	E1	3	Е
										_
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation	
	8	-	III	5 L	F-A. S-B	223 274	E1	Category A SW2	SGG18 SG35	
	•							•	•	-
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	8	-	III	852	5 L	856	60 L	A3 A803	E1	
	8	-	III	Y841	1 L	-	-	A3 A803	E1	1

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

|>SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

|> Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

Container information:

Packaging to be fitted with child-resistant fastenings (see EC Regulation No. 1272/2008, Annex II, Part 3).

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

|> Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH): https://echa.europa.eu/substances-restricted-under-reach.

|> Explosives precursors :

The mixture contains at least one substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors:

- Sodium nitrate (CAS 7631-99-4)

The acquisition, introduction, possession or use of this restricted explosive precursor by members of the general public is subject to the reporting obligations.

IPONE

WHEEL CLEANER 1L - 800656 - A18357

Date: 17/04/2023 Page 13/13 Revision: N°10 (17/04/2023)

Particular provisions:

No data available.

|> Labelling for detergents (EC Regulation No. 648/2004,907/2006):

- less than 5 %: anionic surfactants

- less than 5 %: non-ionic surfactants

15.2. Chemical safety assessment

The chemical safety assessment has not been carried out for this mixture.

|>SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

> Wording of the phrases mentioned in section 3:

H226	Flammable liquid and vapour.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:

EC50: The effective concentration of substance that causes 50% of the maximum response.

Ecx : The effective concentration of the substance that causes x% maximum reaction.

NOEC: The concentration with no observed effect.

REACH: Registration, Evaluation, Authorization and Restriction of Chemical Substances.

DNEL: Derived No-Effect Level

PNEC: Predicted No-Effect Concentration

UFI : Unique formulation identifier. STEL : Short-term exposure limit TWA : Time Weighted Averages

TMP : French Occupational Illness table TLV : Threshold Limit Value (exposure)

AEV: Average Exposure Value.

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

GHS05: Corrosion

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern.

|> Modification compared to the previous version