



FORK 5 -SYNTHETIC PLUS

ODRŽAVANJE

Dostupne gradacije: **5 - 10 - 15 - 20 - 30**

Fork 5 is a semi synthetic lubricant, compatible with all types of forks, for road and off-road use, designed for regular use. IPONE has selected the best synthetic bases and additives to guarantee Fork 5 has a low-friction formula, which ensures comfortable driving and improved shock absorption.



● **PAKOVANJE:**



● **TEHNIČKI PODACI:**

TEST	METODA	VREDNOSTI					JEDINICA MERE
		FORK 5	FORK 10	FORK 15	FORK 20	FORK 30	
GUSTINA NA 20 °C	ISO 12185	0,851	0,866	0,873	0,870	0,870	-
VISKOZITET NA 100 °C	ASTM D445	4	6,2	8,6	10,5	12	mm ² /s
VISKOZITET NA 40 °C	ASTM D445	18,4	37,7	60,2	83,1	102,9	mm ² /s
INDEKS VISKOZITETA (VIE)	ASTM D2270	115	111	115	110	106	-
TAČKA PALJENJA	ASTM D92	192	226	228	228	240	°C
TAČKA KLJUČANJA	ASTM D97	-42	< -36	-36	-27	-27	°C